



// BUTTFUSION FITTINGS

ITEM	CODE	NOMINAL DIAMETERS		
		SDR17/PN10	SDR11/PN16	SDR7,4/PN25
90° elbow	20.10	90 - 315	20 - 315	32 - 160
45° elbow	20.15	90 - 315	32 - 315	32 - 160
90° tee	20.20	90 - 315	20 - 315	32 - 160
90° reduced tee moulded	20.21	125x90 - 200x160	90x63 - 200x160	-
90° reduced tee assembled	20.21	90x50 - 315x250	63x32 - 315x250	63x32 - 160x140
stub end	20.30	40 - 400	25 - 400	20 - 315
cap	20.35	40 - 315	25 - 315	20 - 160
reducer	20.50	40x32 - 315x280	25x20 - 315x280	25x20 - 200x180



// TRANSITION FITTINGS

ITEM	CODE	NOMINAL DIAMETERS	SDR/PN	VERSION AVAILABLE
steel/pe coupling	20.60	25-¾" - 125-4"	SDR11/PN16	galvanized - galvanized with thread - galvanized coated with thread
steel/pe coupling	20.65	140-5" - 315-12"	SDR11/PN16	galvanized
steel/pe coupling with extension and thread	20.61	25-¾" - 63-2"	SDR11/PN16	galvanized - galvanized coated
copper/pe coupling	20.62	25x18 - 32x28	SDR11/PN16	
electrofusion transition socket with brass insert	21.61/21.62	20-½" - 110-4"	SDR7,4/PN25	male/female
transition insert	21.77/21.78	20-½" - 110-4"	SDR7,4/PN25	male/female
electrofusion transition 90° elbow with brass insert	21.65/21.66	20-½" - 110-4"	SDR7,4/PN25	male/female
electrofusion transition 45° elbow with brass insert	21.67/21.68	25-¾" - 110-4"	SDR7,4/PN25	male/female
electrofusion transition socket with brass insert and free nut	21.70	20-½" - 63-2"	SDR7,4/PN25	female
electrofusion transition 90° elbow with brass insert and free nut	21.71	25-¾" - 63-2"	SDR7,4/PN25	female
electrofusion transition 45° elbow with brass insert and free nut	21.72	32-1" - 63-2"	SDR7,4/PN25	female
electrofusion transition spigot saddle with brass insert	21.63	110x - 160x	SDR11/PN16	female - outlet 1" ½ and 2"
electrofusion spigot saddle for shut-off equipment with brass insert	21.64	110x2" - 160x2"	SDR11/PN16	
steel flange covered PP	20.49	25 - 400		PN10 - PN16
aluminium flange	20.40	25 - 400		PN10 - PN16
steel flange	20.45	75 - 400		PN10 - PN16 - PN25
blank steel flange	20.46	32 - 315		PN10 - PN16
stub end/PP flange system	20.47	40 - 315		PN10 - PN16



// ELECTROFUSION FITTINGS

ITEM	CODE	NOMINAL DIAMETERS	SDR/PN
electrofusion socket	21.00.10	32 - 400	SDR17/PN10
electrofusion socket	21.00.16	20 - 400	SDR11/PN16
electrofusion socket	21.00.25	20 - 315	SDR7,4/PN25
electrofusion socket	21.10.10	450 - 630	SDR13,6/PN12,5
electrofusion 90° elbow	21.11.16	20 - 315	SDR11/PN16
electrofusion 90° elbow	21.11.25	20 - 160	SDR7,4/PN25
electrofusion 45° elbow	21.16.16	25 - 315	SDR11/PN16
electrofusion 45° elbow	21.16.25	25 - 160	SDR7,4/PN25
electrofusion 90° tee	21.21	25 - 200	SDR11/PN16
electrofusion reduced 90° tee	21.22	90x63 - 160x110	SDR11/PN16
electrofusion cap	21.36.16	32 - 200	SDR11/PN16
electrofusion cap	21.36.25	20 - 200	SDR7,4/PN25
electrofusion reducer	21.51	25x20 - 200x160	SDR11/PN16
electrofusion spigot saddle monobloc	21.20A	40x20 - 110x63	SDR11/PN16
electrofusion spigot saddle	21.20	50x20 - 250x110	SDR11/PN16
electrofusion tapping saddle monobloc	21.30A	40x20 - 110x63	SDR11/PN16
electrofusion tapping saddle	21.30	50x20 - 250x63	SDR11/PN16
electrofusion tapping saddle with valve	21.73	75x32 - 250x63	SDR11/PN16
fixed handling rod with protection pipe	21.73.50	0,75 - 1,50	
telescopic handling rod with protection pipe	21.73.60	0,80-1,20 - 1,40-2,50	



// ELECTROFUSION WELDING UNITS

ITEM	CODE	TYPE
EURO S1 PLUS	12.12 S1M	all Eurostandard electrofusion fittings
EURO SP1 PLUS	12.19 SPP	polyvalent welding unit - working range d. 20-710
EURO JUNIOR	12.19 JUN	polyvalent welding unit - working range d. 20-160

FOR DETAILED INFORMATION
REFER TO UPDATED “TECHNICAL DATA” MANUAL

