

MTC - Smart Lock for CES2024

1	Product type	Deadbolt	Deadbolt
2	Image		
3	Product	Deadbolt Lock of American Standard	Deadbolt Lock of American Standard
4	Model	LFA501	LA2201B
5	Made in	SHEN ZHEN	SHEN ZHEN
6	Sales type	TO B/C	TO B/C
7	LOGO	Customization	Customization
8	Color	Chrome Plating	YAMA Black、Chrome Plating
9	SKU	Without Fingerprint Type	Without Fingerprint Type、With Fingerprint Type、With Lock Cylinder Type
10	Key Points	Zinc AlloyMetal; Multiple Unlock methods supported; Support OEM/ODM...etc mode; Support HomeKit control (optional); Support Bluetooth unlock; Wide operating temperature to adapt to normal use in lower ambient temperatures; Satisfy ANSI/BHMA RRADE3 standard; Supportportable DIY install.	Aluminum Metal; Multiple Unlock Method supported; SupportOEM/ODM...etc mode; Multiple colors available; Global Networking TUYA APP (optional); Bluetooth unlock supported; Satisfy ANSI/BHMA RRADE3 standard; Portable DIY installation supported; Wide operating temperature to adapt to normal use in lower ambient temperatures.
11	Spec	1、Main Material: Zinc Alloy; 2、Brass B Level marble Lock Core; 3、Stainless steel lock locking case; 4、Unlock Method: Password、Bluetooth、Mechanical Key; 5、Password Capacity: 100SETS; 6、Password figures: 6~10; 7、Number of buttons: 12; 8、Power Supply Method: 4PCS、AA、LR6、Alkaline Dry Battery; 9、Stanby Current: <125uA; 10、Battery Life: >9months; 11、Emergency power supply port: 9V Stacked block battery; 12、Operating Temperature: -31F to 158F (-35°C to 70°C); 13、Operating humidity: 15%RH_93%RHwithout condense; 14、Store Humidity: -31F to 158F (-35°C to 70°C); 15、Flame Retardant Grade: UL 10C; 16、Protection Grade: IP54; 17、Salt Spray Test: 120H; 18、Standard: ANSI/BHMA RRADE3; 19、Door Thickness: 35~55mm; 20、Support distance from door frame: 60/70mm.	1、Main Material: Aluminum; 3、Stainless steel lock locking case; 4、Unlock Method: Password、Bluetooth、Mechanical Key; 5、Password Capacity: 100SETS; 6、Passwordf igures: 6~10; 7、Number of buttons: 12; 8、Power Supply Method: 8PCS、AA、LR6、Alkaline Dry Battery; 9、Stanby Current: <85uA; 10、Battery Life: >18months; 11、Emergency power supply port: USB Type C; 12、Operating Temperature: -31F to 158F (-35°C to 70°C); 13、Operating humidity: 15%RH_93%RHwithout condense; 14、Store Humidity: -31F to 158F (-35°C to 70°C); 15、Flame Retardant Grade: UL 10C; 16、Protection Grade: IP54; 17、Salt Spray Test: 120H; 18、Standard: ANSI/BHMA RRADE3; 19、Door Thickness: 35~55mm; 20、Support distance from door frame: 60/70mm.